



largh. mm	DN	Codice
173	1"	FC0150000010
173	1"1/4	FC0150000012
210	1"1/2	FC0150000015
210	2"	FC0150000020



DISAERATORE FILETTATO

- Corpo: in acciaio zincato;
- Completo di bocchettoni femmina;
- Massimo. esercizio di pressione: 10 bar;
- Massimo. temperatura di utilizzo: 110°C.



THREADED DEAERATOR

- Body: in galvanized steel;
- Complete with female unions;
- Max. pressure exercise: 10 bar;
- Max. temperature use: 110°C



THREADED DEAERATOR

- Corps: en acier galvanisé;
- Complet avec contre-brides;
- Max. exercice de pression : 10 bars;
- Max. température d'utilisation : 110°C.



largh. mm	DN	Codice
000	DN 65	FC0150000065
000	DN 80	FC0150000080



DISAERATORE FLANGIATO PN16

- Corpo: in acciaio zincato;
- Rete disaeratrice in acciaio inossidabile;
- Completo di controflange;
- Pressione max. esercizio: 10 bar;
- Temperatura max. utilizzo: 110°C.



FLANGED DEAERATOR PN16

- Body: in galvanized steel;
- Stainless steel deaerator mesh;
- Complete with counterflanges;
- Max. pressure exercise: 10 bar;
- Max. temperature use: 110°C.



THREADED DEAERATOR

- Corps: en acier galvanisé;
- Maille de dégazeur en acier inoxydable;
- Complet avec contre-brides;
- Max. exercice de pression : 10 bars;
- Max. température d'utilisation : 110°C.