



Cod.	Ø	A	B	C
<b>VA0063000030</b>	3/8"	42	62	52
<b>VA0063000050</b>	1/2"	42	62	52

Temp. Max: 110°C / Max. Temp: 110°C / Température maximale : 110°C

Pressione. Max: 10 bar / Pressure. Max: 10 bars / Pression. Max : 10 barres

 <b>Materiali</b>	
<b>Corpo:</b>	Ottone lega UNI EN 1982:2008 CB754S
<b>Tappo:</b>	Ottone lega UNI EN 1982:2008 CB754S
<b>Galleggiante:</b>	Polietilene
<b>Tappino:</b>	Polipropilene
<b>Or:</b>	NBR70
<b>Meccanismo:</b>	Ottone CW614N
<b>Molla:</b>	Acciaio INOX AISI 302
<b>Sensore:</b>	Acciaio INOX AISI 302
<b>Scodellino:</b>	Resina acetlica
<b>Gommino:</b>	Silicone 50 rosso

 <b>Materials</b>	
<b>Body:</b>	Brass alloy UNI EN 1982:2008 CB754S
<b>Body cap:</b>	Ottone lega UNI EN 1982:2008 CB754S
<b>Floating:</b>	Polyethylene
<b>Cap:</b>	Polypropylene
<b>Or:</b>	NBR70
<b>Mechanism:</b>	Brass CW614N
<b>Spring:</b>	AISI 302 stainless steel
<b>Sensor:</b>	AISI 302 stainless steel
<b>Bowl:</b>	Acetal resin
<b>Rubber:</b>	Silicone 50 red

 <b>Matériaux</b>	
<b>Corps:</b>	Alliage de laiton UNI EN 1982:2008 CB754S
<b>Capuchon du Corps:</b>	Ottone lega UNI EN 1982:2008 CB754S
<b>Flottant:</b>	Polyéthylène
<b>Capuchon:</b>	Polypropylène
<b>Jointts toriques:</b>	NBR70
<b>Mécanisme:</b>	Laiton CW614N
<b>Ressort:</b>	Acier inoxydable AISI 302
<b>Capteur:</b>	Acier inoxydable AISI 302
<b>Bol :</b>	Résine acétalique
<b>Caoutchouc:</b>	Silicone 50 rouge